



*Solution Heat Treat
Furnace Systems*



SECO/WARWICK is a world leader and innovative manufacturer of Solution Heat Treat Furnace Systems with decades of experience. We provide the complete solution to your needs for a custom-designed system.

Many factors contribute to the overall efficiency of SECO/WARWICK's solution heat treating systems. Convection heating using high velocity air distributes heat evenly and efficiently, producing close temperature uniformity. Our time-tested insulation system further enhances efficiency and has proven to be one of the most durable linings on the market today. A variety of circulated airflow patterns add further efficiencies to our furnace designs.



Fully automated solution heat treat and aging system for automotive wheels



Solution Heat Treat Furnace with spray quenching for aluminum extrusions

Capabilities

Our design engineers work closely with your engineering and production staff to ensure optimum performance for your complete furnace system and overall plant operations. We offer complete turnkey capabilities for each project including:

- Foundation Outline
- Solution Heat Treat Furnaces
- Aging Ovens
- Load Handling Systems
- Control Systems
- Automated Product Tracking
- Installation
- Start-up and Testing
- Training

Designed to Fit the Application

SECO/WARWICK uses various designs for recirculating airflow using axial and centrifugal style fans designed specifically for your application, including:

- Horizontal reversing cross flow.
- Longitudinal airflow (or tunnel flow). The recirculated air travels down the length of the furnace or zone of control. This is ideal for mass production of aluminum parts in baskets or on racks.
- Vertical airflow (either upward or downward) is generally used for baskets of small aluminum castings or forgings.

Selecting the proper airflow is dictated by the density and configuration of the load, desired production rate, available floor space, required heating times and temperature uniformity, transport method (if continuous) or load support (if batch), heating method, etc. ANSYS analytical software can be used to evaluate the heating rate of the load prior to selecting the most efficient airflow method. Actual load testing capabilities are available to confirm the theoretical results.

Following heat treatment, load cooling is critical to achieving acceptable metallurgical results. SECO/WARWICK has experience with many different cooling systems. Choices include mobile or stationary dunk-type quenches, elevator type quenching or spray systems. Optional quenching features include motor-driven mixers, heat exchangers, immersion elements and indirect-fired heaters.



Jet Impingement Technology

Jet Impingement Technology provides high-volume production with faster heating rates and tight uniformity using a semi-continuous solution heat treat furnace, water quench and age oven. Faster heating rates get the parts to the soak cycle in less time, reducing the overall cycle. This furnace has achieved temperature uniformity performance as low as $\pm 1^{\circ}\text{F}$ of the temperature set point throughout the soak period. The furnace will load, heat treat, quench and discharge continually without operator assistance.

Continuous Roller Hearth Furnaces

These high-efficiency furnaces provide a competitive edge to producers of aircraft and automotive components, while meeting the most rigid cost and production specifications. Production rates in excess of 16,000 pounds per hour have been obtained in our continuous furnaces.

Continuous furnaces provide flexibility for a wide range of products. By using variable speed drives, the residence time and soak time can be increased or decreased to meet your specific needs.

SECO/WARWICK's unique system of separating the heat and soak chambers with internal doors provides unmatched flexibility and temperature control. By incorporating a discharge chamber, you can unload the furnace without affecting the temperature uniformity of the remaining workpieces. High-speed mechanisms quickly transfer the work to the quench medium.

Control Systems

Control systems supplied with the furnace line will typically include a programmable controller and a personal computer for automatic operation. The process software is written by SECO/WARWICK engineers familiar with solution heat treat processes and load handling requirements. Equipment operation and status can be viewed from our corporate headquarters in Meadville, Pa., with instant online assistance capability.

Plant Support

We offer equipment layout recommendations aimed at economizing space, manpower and operations. To ensure immediate, accurate performance, SECO/WARWICK mechanically and electrically tests each furnace in our facility prior to shipment, unless size prohibits assembly prior to shipment.

Quality Commitment

SECO/WARWICK builds solution heat treating furnace systems for aluminum castings, aluminum plate, aluminum forgings, aluminum extrusions, aircraft applications and billet preheating. With our experience and turnkey capabilities, we will continue to be a world leader and innovative manufacturer of solution heat treating furnace systems. SECO/WARWICK is your complete supplier of heat treating and aging furnace systems.



Solution Heat Treat Furnace equipped with Jet Impingement Technology for aluminum stamping application



Solution Heat Treat Furnace and age oven system for aluminum differential carrier castings



Solution Heat Treat Furnace, front view.



SECO/WARWICK

Meadville, Pennsylvania 16335 USA

Phone: 814-332-8400

E-mail: info@secowarwick.com

www.secowarwick.com

SECO/WARWICK S.A.

66-200 Swiebodzin

Poland

Phone: 48-68-3820-500

E-mail: info@secowarwick.com.pl

www.secowarwick.com.pl

SECO WARWICK Allied Pvt. Ltd.

Mumbai - 400 071. INDIA

Phone: +91-22-2528 4028

E-Mail: allied@alliedfurnaces.com

www.alliedfurnaces.com

SECO WARWICK

Tianjin, China 300402

Phone: 86-22-86853179

E-mail: info@secowarwick.com.cn

www.secowarwick.com

The latest design, materials and equipment specifications should be obtained from the company before any reliance is placed on the enclosed since changes may occur due to product improvement.