

CONTINUOUS HOMOGENIZING





ENHANCED HEAT TRANSFER - VERTICAL AIRFLOW

The high velocity air jet is directed onto the top of each billet which results in higher heat transfer coefficients. Because the furnace consists of multiple zones, it is possible to apply higher air temperatures in each zone without risking damage to the product.

These higher air temperatures combined with higher heat transfer coefficient enables significantly higher convective heat transfer rates into the billets. Because it is possible to operate the zones at a higher temperature without compromising safety, radiative heat transfer is also enhanced. The improved heat transfer results in shorter heat-up times for small and large diameter billets.

UNIFORM QUALITY

The temperature heat treatment process can be optimized as the continuous homogenizing furnace has a material flow with one layer of logs. Quality control is possible for each individual billet has the same performance. The cooling process can also be controlled and optimized.

SECO/WARWICK offer industrial furnaces equipped with advanced technology to reduce cycle times, conserve energy and improve cooling rates. Our five basic product groups include coil/foil anne-aling, solution heat treatment & ageing, log/ingot homogenising and melting/holding furnaces. Each system includes control and material handling packages designed to provide optimum performance in each unique production environment.

With over 50 years of experience working with the aluminium industry, we see your production needs and offer equipment with exceptional quality and value.

AUTOMATIC HANDLING HOMOGENIZING

CONTINUOUS

PRODUCTION FLEXIBILITY


diameters without leaving empty saddles.

Because of its multi-zone design, vertical airflow

furnace technology is inherently flexible. The furnace

can now process batches of different alloys and

the control system. No user interaction is required during normal operation, when a stoppage occurs, or when the furnace needs to be restarted after a stoppage. Stoppages and restarts usually involve significant risks of product damage. Because the process is completely automated, all variations inherent in human control of such a process are eliminated and the consistency of the operation is improved.



The furnace's operation is completely automated by

MODULAR DESIGN - ONE PLANT

The PLC captures detailed historical data (position, temperature, degree of transformation, residence

time) for each billet. The system also makes reports on

single billets and batches of billet available based on

the captured data. The data and reports can be used to

improve the process and to respond to customer

PRODUCT TRACEABILITY

When building the continuous homogenizing plant our design team designs the plant in sections. This means that the plant is delivered to the customer's location in sections, re-assembled and put together. This way of building secures the function of the plant and the installation period is minimized in time to support the production.

ENERGY EFFICIENCY

questions.

The control system constantly optimizes the furnace to perform the highest troughput without empty spaces independent of product mix. A continuous and optimized material flow lead to more efficient energy usage. The counter flow double-pipe heat exchanger recover a considerable amount of the exhaust energy. High-quality packing's and good insulation keep the wall losses to a minimum.

AIRFLOW CONTROL

In the mechanical design process engineers optimize the furnace interior to activate the best possible performance to fulfill our customers different needs.